



Outdoor Event Sound System for 500 Audiences 

★★★★★ [6 Reviews](#)

Outdoor Event Sound System for 500 Audiences
A+
Event Professional Audio DJ Line Array Speaker
PA Sound System with Microphone and Mixer

Price:



\$13,192.17

Quantity:



[PDF Export](#)

Product Description					
packing weight: 050kg					
packing volume: 5cbm					
Item	Description	Model	Specification	Picture	Qty
A1	Line Array	Array-113	Passive two way full range line array LF:1x13.5"(350mm)3"(75mm)/Voice-coil HF:2x1.4"(38mm)each2"(51mm)/Voice-coil Frequency Response: (+/-5dB) 55-19000Hz Coverage Angle: (-6dB) 120°(x)10°V Sensitivity (1m/1W): 102dB SPL 130 (std) ALS/136 (std) Peak Impedance 8 Ohm Power 700W AES /2800W Peak		0
A2	Subwoofer	Array-113S	Subwoofer for line array LF:1x18"(450mm)4"(100mm)/Voice-coil Frequency Response: (+/-5dB) 44-200Hz Coverage Angle: (-6dB) / Sensivity (1m/1W): 96dB SPL 125dB AES/131dB peak Impedance 8 Ohms Power 800W AES /3200W Peak		2

A3	Subwoofer	T-210B	<p>Subwoofer</p> <p>LF 2x18"(460mm)x4"(100mm)Voice-coil</p> <p>Frequency Response (+/-3dB): 30-200Hz</p> <p>Sensitivity (1m²/W) : 101dB</p> <p>SPL131.7dB continuous/137.5dB peak</p> <p>Impedance: 4 Ohm</p> <p>Power: 1200W AES / 4800W PEAK</p>		2
A4	Monitor	T012	<p>LF 1x12"(300mm)x3"(75mm)Voice coil</p> <p>HF 1x1"(25mm)xø1.75"(44mm)Voice coil</p> <p>Frequency Response (+/-5dB)45-18000Hz</p> <p>Coverage Angle (-6dB) 80°Hx60°V(Rotable)</p> <p>Sensitivity (1m²/W) 98dB</p> <p>SPL 124dB AES/130dB peak</p> <p>Impedance 8 Ohms</p> <p>Power 400W AES / 1600W PEAK</p>		2
A5	Monitor	IU12	<p>LF 1x12"(300mm)x3"(75mm)Voice-coil</p> <p>HF 1x1"(25mm)xø1.75"(44mm)Voice-coil</p> <p>Frequency Response (+/-5dB)45-18000Hz</p> <p>Coverage Angle (-6dB) 80°Hx60°V(Rotable)</p> <p>Sensitivity (1m²/W) 98dB</p> <p>SPL 124dB AES/130dB peak</p> <p>Impedance 8 Ohms</p> <p>Power 400W AES / 1600W PEAK</p>		2
A6	Amplifier	A4	<p>800Wx4 @ 8ohm</p> <p>1400Wx4 @ 4ohm</p> <p>1800Wx2 @ 8ohm bridge</p> <p>S/N ratio (20Hz-20kHz) >100dB</p> <p>Sensitivity 0.775V/0dB</p> <p>Voltage Gain (80) 43.2dB</p> <p>Class H Circuit</p> <p>Distortion (低于额定功率1dB, 20-20kHz)</p> <p><0.08%</p> <p>Frequency Response 20-20kHz, +0, -1dB</p> <p>Damping Factor 400</p>		3
A7	Amplifier for Subwoofer	HD-1200	<p>1200W @8ohm</p> <p>1800W @4ohm</p> <p>3500W @ 8ohm bridge</p> <p>S/N Ratio (20Hz-20kHz) 110dB</p> <p>Sensitivity 1.0Vrms</p> <p>Voltage Gain (80) 39.8dB</p> <p>Class D circuit</p> <p>Distortion (低于额定功率1dB, 20-20kHz)</p>		2

BD $\pm 0.07\%$, 4D $\pm 0.1\%$
 Frequency Response 20-20kHz,
 $\pm 0.5\text{dB}/\pm 0.5\text{dB}$
 Damping Factor 200

Item NO.	Description	Model	Specification	Picture	Qty
B1	12 channel Mixer	MT-12D			1
B2	Processor (4 in, 8 out)	DP-4SS			1
B3	Wireless Microphone (hand held)	M-3C0A/M1			2
B4	Wireless Microphone (Ear-worn)	M-3C0A/M2			1
B5	Wireless Microphone (Go-cip)	M-3C0A/M3			1
B6	Power Sequencer	PSC108			2

					
B7	Line array susceptor	PRO-A113			2